




WireCo[®]
WorldGroup

Premier Crane Ropes


Starlift Plus

A premier hoist rope for main and auxiliary hoist applications on tower cranes, mobile cranes and crawler cranes as well as other applications where rotation resistant ropes are required. Especially suited for multiple layer spooling.




NR Maxipact

All cranes and performance lifting devices where non-rotating and high MBL ropes are required. Recommended for offshore, deck cranes and marine environment. Option PPI available for diameter ≥ 13 mm




Turboplast

Boom hoist rope for mobile cranes, deck cranes and grabs, hoist rope for container cranes, floating cranes, portal cranes, steel mill cranes, etc. In multiple part reeving for smaller lifting heights, twin hoist systems with left and right hand lay ropes for greater lifting heights, riser tensioner, where rotation resistant ropes are not required.



HDS K PPI

When rotation resistant ropes are not required (twin hoist systems with right and left ropes, small heights). Hoist for steel mill cranes, container cranes, floating cranes and boom hoist for deck cranes, luffing and mobile cranes, grab cranes.



WireCo WorldGroup provides a broad variety of end terminations and services:

- Socketing of ropes with hot metal or resin
- Casting of multi-strand or retraction ropes with high demands on the exact length of each rope
- Loops with pressed aluminum ferrules
- Spliced loops
- Flemish eyes
- Pressed thimbles
- Special designed steel pressings that fulfill a multitude of special specifications
- Becket loops
- Special mounting eyes
- Select crane OEM specific end terminations